

ARGUS® 260

B R O A D B A N D T E S T E R

GPON

XGS-PON

xPON-ID

FTTH

**PON
Installation**

**Sel.
OPM**

FIT

OLTS

VFL

G.fast

VDSL

ADSL

Bonding

2.5GigE

SFP

WLAN

POTS

ISDN

Data
101101011011

Cu

**IP
TV**

TDR

**Vo
IP**

RFL

**Speed
test**

**Remote
kit**

iperf

**Line
Scope**

**RFC
6349**




data sheet: technical data subject to change.

TEST EQUIPMENT
MADE IN GERMANY

intec

GESELLSCHAFT FÜR
INFORMATIONSTECHNIK mbH

Where to use the ARGUS?



ARGUS® 260: The broadband tester

The new ARGUS® 260 all-in-one tester delivers improved performance for testing broadband interfaces. The high-quality multifunction tester is ideally equipped for the expansion of future networks.

Modern design and new housing concept

Its robust design combines the requirements for a compact hand-held meter in daily field use with the performance of a high-end tester. As the first ARGUS® tester with touch-screen display, it enables intuitive navigation of the familiar ARGUS® menu structure. Thanks to the use of numerous graphical elements, the redesigned GUI makes this sophisticated multifunction tester as easy to use as a smartphone. A new, innovative internal help function supports rapid, reliable interpretation of test results.

All necessary broadband interfaces

The ARGUS® 260 reliably tests all broadband interfaces, from GPON, XGS-PON and G.fast (106 + 212 MHz) to super vectoring, Bonding, ADSL and VDSL accesses, in the uncompromising quality you have come to expect. It is also equipped with a wide range of further interfaces and test functions, such as 2.5 Gigabit Ethernet, WLAN, copper, TDR, RFL, triple play and many more.

Additional features

The integrated WIFI interface enables the ARGUS® 260 to communicate with its environment directly - a PC link is no longer required.

Once integrated in your job management system, the ARGUS® 260 marks the advent of a new generation of broadband testing.

intec Gesellschaft für Informationstechnik mbH

For over 35 years, intec Gesellschaft für Informationstechnik mbH has stood for innovative measurement technology - developed and produced for telecommunications networks in Europe. Our ARGUS® testers make fiber optic and broadband infrastructures accessible, document efficiently and support daily maintenance and troubleshooting in fiber optic and copper networks as well as via Ethernet. We deliver what network operators and service technicians need: speed, security and trust.

Our solutions are optimally adapted to European standards, norms and protocols. Linguistic and technical localization, fast shipping within the EU and direct technician support guarantee short distances and fast help without detours. For us, "Made in Europe" stands for quality, transparency and sustainability. Thanks to modular, scalable products, we serve both small companies and large network operators. Long-term product maintenance and regular updates make your investment future-proof.

We are driven by our innovation: We integrate the latest technologies such as GPON, XGS-PON, ADSL2+, VDSL2 vectoring, VDSL2 bonding, VDSL2 profile 35b or G.fast (profile 106a and 212a) and are constantly developing our portfolio. This means that ARGUS® testers are ideally equipped for current and future requirements. Our user interface is based on freely configurable tiles: technicians start directly with the appropriate measurement configuration - simple, fast and error-free. Clearly displayed results are transmitted via WLAN to smartphones, central servers or the ARGUS® app. Supervisors can also take over devices remotely and provide active support. Central management and archiving of test results make it easier to handle large network structures - significantly reducing training costs and error rates.

Our ARGUS® testers have been sold over 100,000 times - including to leading European network operators such as Deutsche Telekom, Vodafone, Telefónica, KPN, BT and Telekom Austria.

Specification Broadband Interfaces:

General:		Application, Settings + Results:	
G.fast Tester	G.fast Modem Simulation, FTU-R, CPE G.fast Bridge + G.fast Router ITU-T G.9700/9701 Profile 106a/212a Time Division Duplexing (TDD)	G.fast / VDSL / ADSL - Net Data Rate d/u [kBit/s] - Attainable Data Rate d/u [kBit/s] - Relative Capacity d/u [%] - SNR Margin / Loop Attenuation d/u [dB] - Output Power d/u [dBm] - Interleave Delay d/u [ms] - Impulse Noise Protection d/u [Symbols] - FEC + CRC, far/near [Errors] - ES, SES, LOSS + UAS, far/near [sec] - Reset /Resync [Number] - Bitswap Events d/u - Retransmission d/u (G.INP) - Vendor, far/near [Name/ Number] - Modem Trace - Bits/SNR/QLN/Hlog/Noise Graphs - OK /Fail Evaluation: Bitrate, CRC, FEC - DC Voltage, UDC	G.fast / VDSL - Signal Attenuation [dB] - Showtime no Sync [Number] - Seamless Rate Adaption (SRA) - Data Transmission Unit (DTU) - INP REIN + INP SHINE [Symbols] - Expected Throughput Rate (ETR) [kBit/s] - Electrical Length @1 MHz R/C [dB] - EFM Statistics: Frames + Bytes VDSL - Vectoring Mode - Graphical Long-time Trace in ARGUS® ADSL - Latency Mode - Graphical Long-time Trace in ARGUS®
VDSL Tester	VDSL2 Modem Simulation, VTU-R, CPE VDSL2 Bridge + VDSL2 Router ITU-T G.993.2 (Profiles 8, 12, 17a, 30a) ITU-T G.993.2 Annex Q (Profile 35b), Super Vectoring (Vplus) ITU-T G.993.5, G.vector (Vectoring) ITU-T G.998.4, G.INP (Retransmission) ITU-T G.998.2, G.bond, 35b Bonding		
ADSL Tester	ADSL Modem Simulation, ATU-R, CPE ADSL Bridge + ADSL Router ITU-T G.992.1, Annex A+B (ADSL) ITU-T G.992.2, Annex A (G.lite) ITU-T G.992.3, Annex A+B+L+M (ADSL2) ITU-T G.992.5, Annex A+B+J+M (ADSL2+)		
GigE Tester	Ethernet according to IEEE 802.3 1 x 10/100/1000 Base-T (RJ45/8P8C) • 2.5 GBase-T (IEEE 802.3bz, NBase-T) 1 x SFP Interface, supports: • 1000 Base-BX/LX/SX/ZX • 2.5 GBase-X (IEEE 802.3bz, NBase-T) • FTTx (PtP), Active Ethernet DDM according to SFF-8472	- Link Status, Autonegotiation, far/near - Auto-MDI(X) Function - Speed (10, 100, 1000 Mbit/s) - Duplex Mode (full, half) / Flow Control - Polarity/Wire Pair (+/-) - Pair skew/Wire Pair [ns] - Frames (Rx/Tx) [Number] - Errors, Bytes (Rx/Tx) [Number] - Collisions [Number]	- SFP: Digital Diagnostic Mode (DDM): - Manufacturer Name, OUI, Item Number, Revision, Serial Number, Date, Coding, Medium, Speed - Optical Level (Tx/Rx), ±3 dB - Optical, PWR (Tx/Rx), ±3 dB - Temperature, Voltage, Current (Tx) - Max. Cable Length (Cu, SM, MM/OM1-4)
GPON Tester	GPON Modem Simulation, ONT, CPE ITU-T G.984 via ARGUS® GPON ONT • GigaBit Passive Optical Network DDM accord. to SFF-8472 (see Ethernet)	- Link Status / Link Speed - ONT Status / OLT Tx Power - Optical Network Unit ID (ONU ID) - Passive Optical Network ID (PON ID, Vendor + Equipment ID / Version) - GPON Modem Trace - Serial Number / Password Configurable	- Scan PLOAM message (ONU ID, S/N)* - SFP: Digital Diagnostic Mode (DDM) - Measuring range at 1490 nm: -8 to -30 dBm - Accuracy at -20 dBm: ±0.5 dB, calibrated - Optical Line Attenuation in dB
XGS-PON Tester	XGS-PON Modem Simulation, ONT, CPE ITU-T G.9807.1 via ARGUS® XGS-PON ONT • GigaBit Passive Optical Network	- Link Status - ONT Status / OLT Tx Power - Optical Network Unit ID (ONU ID) - Passive Optical Network ID (PON ID, Vendor + Equipment ID / Version) - XGS-PON Modem Trace - Serial Number / Password Configurable	- Scan PLOAM message (ONU ID, S/N)* - SFP: Digital Diagnostic Mode (DDM) - Measuring range at 1577 nm: -7 to -34 dBm - Accuracy -20 dBm: ±0.5 dB, calibrated - Optical Line Attenuation in dB
PON installation test	GPON installation test PON level check	- guided measurement sequence - target attenuation can be entered as threshold value - automatic OK /Fail evaluation - PDF measurement protocol - SFP parameters (s. Eth/GPON)	- calibrated measurement of the insertion loss with ±0.5 dB accuracy - Assistance for up to 64 fibers - Evaluation PON-ID - Query of the job data
WLAN	WLAN Access Point Mode WLAN Client Mode - via int. opt. interface - Tri-Band (2.4; 5 and 6 GHz), 2x2 - WiFi7 (IEEE802.11 a/b/g/n/ac/ax/be) - via ext. USB stick, max. - Dual-Band (2.4 and 5 GHz), 2x2 - WiFi5 (IEEE802.11 a/b/g/n/ac) - WiFi6e (IEEE802.11 a/b/g/n/ac/ax) - WiFi6/7 detection (IEEE802.11 ax/be) - WPA2/WPA3 Personal/Enterprise, OWE	- WLAN Access Point Scan - Number / List Access Points - Number 2.4 GHz / 5 GHz Networks - Network/Name (SSID) - Signal Strength (RSSI) [dBm] - Signal Quality [%] - MAC Address of AP - Used Channel/Frequency - Used Protocol - Negotiated Encryption - Authentication - Group Cipher, Pairwise Cipher	- Access Point Mode (WLAN Router) for mobile devices - IP Tests (Data, VoIP, IPTV) - AP Management (save etc.) - Test Result Upload via Web Server, WebDAV and FTP - Configuration Download via WebDAV and FTP - Remote Control via VNC, Web Server - Firmware Update via FTP Download
ARGUS® WLAN Analyzer	- Displaying the networks during existing WLAN connection - Manual evaluation of channels possible in tabular and graphical form	Searching for networks again during existing WLAN connection	Advanced automated evaluation of found networks and display of all AP info
WLAN spectrum analysis	optional: ARGUS® 2G4 Scope graph. WLAN spectrum analysis for 2.4 GHz for the specific WLAN trouble-shooting	- Real-time Analysis /Graphics - passive (no WLAN Interference) - Channel Load - Graphical representation	- Detection of - Bluetooth Devices - Motion Sensors - Microwave Ovens - Baby Phones

data sheet: technical data subject to change.

Specifications Protocol and IP tests (Triple Play):

General:		Applications, Settings + Results:	
Protocol Tests		- Configurable MAC Address - Use of Virtual Lines (VL): Maximum Flexibility as well as Control and Priorization under Real Conditions by Several VLs simultaneously - One VL/Service each (Data, VoIP, IPTV, opt.) - VL Configurable in Profiles (20) - IP, PPPoE via xDSL, G.fast + Eth (PPTP) - EoA, IPoA, PPPoA via ADSL - VPI/VCI, VLAN (Modus, ID, Prio., TPID) - PPP Profiles (Username, Password) - IP Version (IPv4, IPv6, Dual) + DHCP - Automatic receiving of connection-dependent dial-in data: PPP, VoIP (phone number)	- Display of BRAS Information - AC Name, Service Name, Session ID - Display of PPP Information - PPP Packets/Bytes (Tx/Rx) - PPP Trace (PPP Commands, Time) - Display of IP Information - IPv6: Global Unicast/Link Local Address - IPv4: Assigned IP, Gateway, DNS - Recording of a Data Log for Evaluation on PC (e.g. Wireshark)
Data Tests (Download Tester) PC/Terminal Simulation IP Ping Test Traceroute Test HTTP Up-/Download Test FTP Up-/Download Test FTP Server Test Webbrowser ARGUS® Real Speed Formal (RFC6349) ARGUS® Real Speed Direct (iperf)		- Memory with up to 10 IP Addresses, (IPv4/6 Address as Number or Name) - Number of Pings, Pause Configurable (Ping), Packet Size + Fragmentation Configurable - Traceroute: Max. Hops, Probes + Timeout Conf. - Down-/Upload: Server Profiles (10): Server Addr., File Name/Size, Number, Number of Parallel Downloads Configurable - FTP: Username + Password - Display Results IP Ping - Display of Packets (Tx/Rx/repeated) - Checksum Error [Number] - Error Packets [Number] - Display Results Traceroute - Current Hop + Probe / List of Hops - Response Time of Hops [s] - IP Address of Current Hops	- Round Trip Time (min/max/avg) [ms] - Display Results Down-/Upload - Current/Total Number [Number] - Already Loaded Data [%] - Average Speed [Mbit/s] - Loaded Bytes [MB] - Transfer Time /Remaining Time [h:min:s] - ARGUS® Real Speed Direct (iperf) - Speedtests up to 10 Gbit/s, depending on utilization (min. 1 Gbit/s guaranteed) - Client /Server Mode - TCP Throughput Down-/Upload - ARGUS® against ARGUS® - ARGUS® Real Speed Formal (RFC6349) - Throughput Test - Evaluation according to RFC 6349
VoIP Tests (VoIP Tester) IP Telephone Simulation Testing of VoIP Connections incl. Acoustics (dif. Codecs) MOS Evaluation (ITU-T P.800) Call Generator (up to 30 Calls)		- Configuration in VoIP Profiles (20): SIP Username, Password, Registrar Server, Outbound Proxy/SBC, Domain, Listen + Remote Port, Authentication, Caller ID, User Agent, Qualify, Process of Registration - Phone Settings: RTP Port Area, Silence Detection, Jitterbuffer, Codecs, DTMF - STUN Server - MOS Threshold for OK/Fail Evaluation - VoIP QoS, Layer 3 Diffserv: RTP/SIP: ToS, DSCP - VoIP QoS, Layer 2 VLAN Prio.: RTP/SIP: VLAN Prio. - Codecs: G.726 (16/24/32/40), G.729 (A/B), G.711 (a-law/μ-law), G.722 - Display of Own Number, Number of Called Person	- Duration of Connection [h:min:s] - MOS Plain Text Evaluation, According to E Model R Factor, ITU-T G. 107 (current/avg), MOS (current/avg/min/max/ideal) - Statistics: RTP Packets (Tx/Rx), - Error Counter: RTP Drop, RTP Error - RTP Jitter Rx (current/avg/min/max) - Lost RTP Packets (avg/min/max) - RTCP Contents: - RTP Jitter far (current/avg/min/max) [ms] - Lost RTP Packets of Remote Side - Network Delay (current/avg/min/max) [ms] - Display of Registration Details: SIP Codes, Registrar IP, Proxy, URI - Simulation (VoIP NT)
IPTV Tests (IPTV Tester) IPTV Device Simulation IPTV STB Simulation (Set-top Box) OK/Fail Evaluation IPTV Channel Scan IPTV Monitor (IPTV passive)		- Configuration in IPTV Profiles (3): Editable Channel List (up to 250 Channels), Multicast IP + Port, Channel Name, IGMP version - Thresholds for IPTV OK/Fail-Evaluation: IGMP Latency, Sync Error, PCR Jitter, Error Indication, CC Errors, CC Error Rate, Audio + Video Bytes, RTP Jitter, RTP Sequence Error, Current + Total RTP Loss Rate - Different VLs for IGMP + RTP - Scan Profiles (3) Configurable: max. Zapping Time - Display of Selected IPTV Channel, Test Duration, current Bitrate, OK or Fail - Packets Loss (current/min/max/avg) [Number]	- RTP/UDP Packet Loss Rate [%] - Delay [ms] + Delay Factor [ms] - Media Loss Rate (MLR) [%] - IP Address of Channel + Port - IGMP Latency (Activation Time) [ms] - For Correlation: xDSL CRC Counters - RTP Errors, RTP Sequence Errors - MPEG Bitrate + Packets (min/max/...), Bytes (current/min/max/...), PCR Jitter (current/min/max/avg) [ms], CC Errors + Error Rate (current/max) [%], Error Sync + Indication - Codecs and PIDs (Packet Identifier) - Channel Zapping Time (min/max/avg) [ms]

data sheet: technical data subject to change.

Specifications Fiber Tests:

General:	Applications, Settings + Results:	
ARGUS OPM Optical Power Meter	- Optical Power Meter in SFP form factor - Powerful InGaAs Photo Diode - Optical Level Measurement with wavelengths from 850, 1300, 1310, 1490, 1550, 1610, 1650 nm - Measuring range: -60 dBm up to +6 dBm, ± 0.25 dB	
Selective xPON-OPM for GPON / XGS-PON 3xOPM	- Measuring range: 1577 & 1490 nm (filtered): from -40 to +6 dBm (max. power +18 dBm) 1270, 1300, 1310, 1550, 1610, 1625 nm (broadband): from -50 to +13 dBm (max. power +18 dBm) - Accuracy: ± 0.5 dB - Calibration conditions: -20 dBm, 23°C ± 5 K - Connector: SC/APC, SFP+, LAN4 10 GBase-T - Readout of PON ID and XGS-PON ID* via SC/APC, detection up to: - GPON ≥ -29 dBm - XGS-PON ≥ -30 dBm	- Live display of the level - Storage of the measurement in measurement protocols - Robust and protected by use in SFP slot - Optional Calibration at 1310, 1490 and 1550 nm (-20 dBm), 20 °C - Remote control of the OLS with switching of the wavelengths and transmission of the transmission power via TWIN mode (only in conjunction with OLS)
Selective Through Mode xPON-OPM for GPON/ XGS-PON 4xOPM opt. 5xOPM	- Measuring range: - Downstream (OLT socket): - 1577 & 1490 nm (filtered): from -40 to +9 dBm (max. power +18 dBm) - Upstream (ONT socket): - 1310 & 1270 nm (filtered): from -35 to +10 dBm (max. power +18 dBm) - opt. 1550 nm (filtered): from -40 to +16 dBm (max. power +18 dBm) - Accuracy: filtered ± 0.5 dB - Insertion loss: 1.5 dB - Alien ONT detection (burst + permanent) - Calibration conditions: -20 dBm, 23°C ± 5 K	- Full ONT simulation (GPON ONT or XGS-PON ONT) via additional GPON/XGS-PON SFP transceiver module - IP/Performance tests via SFP+, LAN4 10/5/2.5/1 GBase-T, 100Base-Tx with up to 1 Gbit/s (max. 2.5 Gbit/s) - Remote control of the OLS with switching of the wavelengths and transmission of the transmission power via TWIN mode (only in conjunction with OLS) * The network must provide the ID for this.
	- Connector: 2x SC/APC (ONT + OLT), SFP+, LAN 10 GBase-T - Full ONT simulation (GPON ONT or XGS-PON ONT) via additional GPON/XGS-PON SFP transceiver module - Readout of PON ID and XGS-PON ID* via SC/APC, detection up to: - GPON ≥ -30 dBm - XGS-PON ≥ -29 dBm - IP/Performance tests via SFP+, LAN 10/5/2.5/1 GBase-T, 100Base-Tx with up to 10 Gbit/s (opt.) * The network must provide the ID for this.	

data sheet: technical data subject to change.

External extensions:

General:		Applications, Settings + Results:
Fiber Inspection Tool Video Microscope	• USB Microscope for the ARGUS • optical Fiber Inspection • manual Focusing with separate key • optional: Autofocus • digital Zoom • Pass /Fail evaluation according to IEC 61300-3-35	• min. Particle Size 0.5 µm • Defects: Core, Cladding, Adhesive, Contact • Scratches: Core, Cladding, Adhesive, Contact • different Tips /Adapters included in scope of delivery • PC, UPC, APC • Single Mode /Multi Mode
VFL Visual Fault Locator	• Mini Visual Laser Source • Output Power: 1 mW • Detecting Range: about 5 km • Wavelength: 650 nm	• Laser Level: Class 2 • Connector: Un/FC • Modulation Frequency: CW / 2 Hz • Power Supply: 2 * AAA batteries
Optical Light Source	• Wavelength: 1310 nm, 1490 nm, 1550 nm +1625 nm (± 20 nm) • Stability: - Short term (15 minutes): 1310 nm < ±0,05 dB 1490 nm < ±0,10 dB 1550 nm < ±0,05 dB 1625 nm < ±0,10 dB - Long term (5 hours): 1310 nm < ±0,10 dB 1490 nm < ±0,20 dB 1550 nm < ±0,10 dB 1625 nm < ±0,20 dB • Connector: SC/APC with dust protection and protection against loss • Spectral width: 5 nm • Frequency: 270 Hz, 1 KHz, 2 KHz	• Auto wavelength: protocol-based wavelength and TX power transmission • Power: -5 dBm ±0.5 dB • Auto power off / backlight • Power supply: 2x Ni-MH AA (2500 mAh), AC/DC charger • Dimension (L x W x H): 160 x 76 x 45 mm • Net weight: 270 g • Accessories: AC/DC charger, 2 x AA battery • Remote control of the OLS with switching of the wavelengths and transmission of the transmission power via TWIN mode (only in conjunction with ARGUS OPM) • ARGUS® can be enhanced with an Optical Loss Test Set (separate option)

data sheet: technical data subject to change.

Specifications ISDN:

General:	Applications, Settings + Results:	
BRI S Interface ITU-T I.430 BRI S Terminal BRI S Telephone BRI S TE Simulation	• BRI S TE Mode, Terminal device simulation • Autom. Detection of Connection Configuration • L2 Mode: automatic, P-P, P-MP • Test Availability of B Channels • BRI S Level and Voltage Evaluation • Protocol: DSS1	• Display L1, L2 and L3 of B Channel Status • incoming /outgoing Call • Display of Call Parameters • own Acoustics • Connection: Call (Single/Block Dial)

Specifications POTS:

General:	Applications, Settings + Results:	
POTS Tester Analogue Tester POTS Butt Set POTS Terminal Simulation POTS Monitor	• Fully-fledged POTS Butt Set, POTS Phone • POTS Terminal Equipment (TE) • Analogue Phone w/ DTMF + Pulse Dial • Incl. Fully-fledged Analogue Acoustics • High-impedance Listening on POTS • Configurable DTMF Signal Level	• Voltage Measurement + Display Polarity when Hook-on and Hook-off • CLIP + Caller-ID according to ETS 300 659/778 • Supports FSK + Display of Caller ID • FLASH Function (40 up to 1000 ms)

data sheet: technical data subject to change.

Specifications Cable Multimeter:

General:			
	Measuring Range	Resolution	Accuracy
DC Voltage; UDC (U =):	• 0 V to 9.99 V	• 0.01 V	• ± (0.5 % + 2 digits)
	• 10 V to 200 V	• 0.1 V	• ± (0.5 % + 2 digits)
AC Voltage; UAC (U ~):	• 0 V to 9.99 V	• 0.01 V	• ± (2 % + 2 digits)
	• 10 V to 200 V	• 0.1 V	• ± (1.5 % + 2 digits)
Frequency: 10 Hz to 200 Hz; 0.2 Hz; ±(1.5 % + 2 digits), sinus			
Capacitive Symmetry Balance; CSym:	• 10 nF to 4 µF	• 0.01 nF	• 0.1 % of the capacity against ground
Dielectric strength for external voltage up to 17 V DC or 17 V AC (with a load 200 kΩ).			
Capacitance; C:	• 0.01 nF to 9.99 nF	• 0.01 nF	• ± (4 % + 4 digits)
	• 10 nF to 99.99 nF	• 0.01 nF	• ± (4 % + 4 digits)
	• 100 nF to 999.9 nF	• 0.1 nF	• ± (3 % + 1 digit)
	• 1 µF to 8 µF	• 1 nF	• ± (3 % + 1 digit)
Dielectric strength for external voltage up to 17 V DC or 17 V AC (with a load 200 kΩ). Measured by film capacitors.			
Isolation Resistance (105 V, max. 2 mA); Iso:	• 0.1 kΩ to 99.9 kΩ	• 0.1 kΩ	• ± (2 % + 1 digit)
	• 100 kΩ to 999 kΩ	• 1 kΩ	• ± (2 % + 1 digit)
	• 1 MΩ to 9.99 MΩ	• 10 kΩ	• ± (2 % + 1 digit)
	• 10 MΩ to 99.9 MΩ	• 100 kΩ	• ± (5 % + 1 digit)
	• 100 MΩ to 1 GΩ	• 100 kΩ	• ± (5 % + 1 digit)
Dielectric strength for external voltage up to 5 V DC or 30 V AC (with a load 200 kΩ).			
Isolation Resistance (8 V, max. 8 mA); Iso:	• 0.1 kΩ to 99.9 kΩ	• 0.1 kΩ	• ± (2 % + 1 digit)
	• 100 kΩ to 999 kΩ	• 1 kΩ	• ± (2 % + 1 digit)
	• 1 MΩ to 9.99 MΩ	• 10 kΩ	• ± (2 % + 1 digit)
	• 10 MΩ to 40 MΩ	• 100 kΩ	• ± (5 % + 1 digit)
Dielectric strength for external voltage up to 5 V DC or 30 V AC (with a load 200 kΩ).			
Resistive Symmetry Balance; RSym:	• 10 Ω to 5 kΩ	• 0.1 Ω	• 0.2 % of Rs ± 0.2 Ω
Dielectric strength for external voltage up to 30 V DC or 30 V AC (with a load 200 kΩ).			
Loop Resistance; R: (13 V, max. 15 mA)	• 1 Ω to 999.9 Ω	• 0.1 Ω	• ± (1 % + 3 digits)
	• 1 kΩ to 9.999 kΩ	• 1 Ω	• ± (1 % + 1 digit)
	• 10 kΩ to 99.99 kΩ	• 10 Ω	• ± (1 % + 1 digit)
	• 100 kΩ to 999.9 kΩ	• 100 Ω	• ± (1 % + 1 digit)
	• 1 MΩ to 9.999 MΩ	• 1 kΩ	• ± (2 % + 1 digit)
	• 10 MΩ to 40 MΩ	• 10 kΩ	• ± (5 % + 1 digit)
DC Current; IDC (I =):	• 0 mA to 150 mA	• 0.1 mA	• ± (2.5 % + 3 digits)
Unbalance @ 1 MHz; LCL:	• 0 dB to 55 dB	• 0.1 dB	• ± 1.5 dB
	• 55.1 dB to 65 dB	• 0.1 dB	• ± 3 dB
The length of the test leads can influence the accuracy of the measurement. Dielectric strength for external voltage up to 3 V DC or 3 V AC. At an internal resistance of the source of 1 MΩ it will be measured up to 3.5 V DC / AC.			

data sheet: technical data subject to change.

NEXT @ 1 MHz; NEXT:		• 0 dB to 65 dB	• 0.1 dB	• ± 1 dB
Dielectric strength for external voltage up to 3 V DC or 3 V AC. At an internal resistance of the source of 1 MΩ it will be measured up to 3.5 V DC / AC.				
RFL Resistance troubleshooting	• Display of: - Resistance to error (R _x), distance to error - Resistance from fault to short-circuit (R _y) - Loop resistance (R _s), cable length - Fault resistance (R _{fault})	• Measuring ranges: - Loop resistance (R _s): 10..9999 Ω - Fault resistance (R _{fault}): 0..20 MΩ	• Accuracy R _x at L _x /L = 0.1 - R _s = 2000 Ω: ± 0.3 % ± 0.05 Ω - R _s = 200 Ω: ± 1.0 % ± 0.06 Ω	
Remote Kit Control	• Use ARGUS to control different Remote Kits to switch the Line on the remote side, e.g. TX916 - Short-circuit - Exchange connect - Open circuit - Loop - Tone mode - switch 2 ports simultaneously			
Other Functions:	• Autotest	• Fast cable check	• Signature detection (e.g. PPA)	
Reference Conditions (calibration):	• Temperature: 23 °C ± 5 °C • Relative humidity: 50 % ± 20 % relative humidity, non-condensing		• Frequency of measurement type: 50 Hz ± 5 Hz, sinus	

Specifications Copper Tests

General:	Applications, Settings + Results:	
TDR Test Time Domain Reflectometer	• Determination of the Loop Length • For Identification and Detection of Shorts, Opens, Impedance Mismatches, Bridged Taps/Stubs, Moisture, Loading Coils, Loose Contacts and more • Pre-configured List of Cable Types, Velocity of Propagation (VoP): 30 % (45 m/μs) up to 99.9 % (149.7 m/μs), Line Resistance, Mutual Capacitance • Measurement Range: 3.5 up to 6000 m	
Line Scope DSL Spectrum Analysis DSL Oscilloscope RF Current Clamp	• Monitoring in Time/Frequency Domain on all Types of Lines for Telecommunications and on active Lines with up to 200 VDC and 40 Vpp • Modem Finder, via Handshake Tones • Frequency Range: 20 kHz up to 35 MHz • Resolution: 67 Hz up to 8.625 kHz or 0.025 % of Measurement Range, Accuracy: ±2 dB • High-impedance or Line Termination: - Input Impedance: 3.6 kΩ, <10 pF - Switchable 100 Ω Input Resistance • Config. Gain FFT: -26 dB up to +20dB	• Res.: 0.025 % of Measurement Range; Accuracy: ±2 % • Graphical Display of Reflection Course • Configurable gain: -26 dB up to +44 dB • Config. Pulse: 5 ns up to 3.2 μs, Pulse Height: 5 V and 20 V • Dynamic range: 60 dB / Amplification Level • Zoom + Cursor for a Detailed Analysis • Save + Set of Reference Curve • Start/Stop Function (Realtime Mode)

data sheet: technical data subject to change.

Documentation and Analysis
• Documentation of all parameters recorded to test reports (in device and on PC) via automatic access tests • Transfer of test results via QR code to a smartphone or via WLAN, ETH or DSL to cloud (FTP server) • Transfer of measurement results to the ARGUS® Mobile App • Free of charge firmware updates via cloud or ARGUS update tool (www.argus.info) • WLAN for transf. test results to systems of an electronic order processing system, remote control via smartphone

Device Specifications
Technical Features: • Hotkey Quick start of various tests • Power management User configurable • Keypad 18 keys, 4 cursor keys, 4 context-sensitive softkeys • TFT colour display 800 x 480 pixels, backlit, incl. touchscreen • 6 LEDs Indicating the status + Ethernet port LEDs • Handset Integrated earpiece and microphone • ARGUSpedia Integrated help function • CE marking Complies with CE directives • User safety Fulfills EN 62368-1 • RoHS conformance Conformance according to WEEE directive
Interfaces: • 1x RJ-45, 1x RJ-11 For xDSL, G.fast, POTS, U, R and C Measurement • 1x Ethernet 10/100/1000 Base-T/ 2.5 GBase-T, RJ-45 test port • 1x SFP port 1000 Base-SX/LX/ZX/BX, 2.5 GBase-X • USB interfaces 2x USB 2.0 host type A, 1x USB 2.0 client type micro B • WLAN IEEE802.11a/b/g/n /ac , ax detection
Environmental conditions: • Temperature range for charging battery pack 0 °C (+32 °F) up to +40 °C (+104 °F) • Max. Operating temperature (endurance tests) 0 °C (+32 °F) up to +40 °C (+104 °F) • Max. Operating temperature (in battery mode) -10 °C (+14 °F) up to +50 °C (+122 °F) • Operating temperature (with power/car adapter) 0 °C (+32 °F) up to +40 °C (+104 °F) • Storing Temperature -20 °C (-4 °F) up to +60 °C (+140 °F) • Relative humidity Up to 95 %, non-condensing
Dimensions: • Size H x W x D: 300 x 128 x 84 mm (11.81 x 5.04 x 3.31 in) • Weight <1.500 g (3.31 lbs) ARGUS incl. battery pack

data sheet: technical data subject to change.

Standard Package:		
Basic device incl. Gigabit-Ethernet interface (10/100/1000 Base-T), ADSL (Annex A+L+M) + VDSL2 (up to profile 35b), Bridge/router mode, Wi-Fi-Management, IP+Download package (IP ping, traceroute test, HTTP/FTP download, FTP upload/server), Line scope, Network scan, Web browser, Cloud services, Lithium-Ion battery pack, Mains adaptor, Shock absorbing rubber jacket, Carrying case, 2 wire cable + xDSL adaptor, Micro USB cable, Carrying strap, Hand strap and English manual		
Additional Options:		
• ADSL Annex B + J Enhancement		Order number: 026008
• VDSL2 Bonding Enhancement (up to Profile 35b)	requires Art.No.: 026045, incl. Bonding Cable	Order number: 026050
• G.fast Enhancement (Profile 106a and 212a)		Order number: 026045
• Time Domain Reflektometer option (TDR)	up to 6 km	Order number: 026040
• Copper Package (Cable Multimeter/DMM)	incl. banana cable red/black + green	Order number: 026010
• Resistive Fault Location option (RFL)	requires Art.No.: 026010	Order number: 026055
• ARGUS® RF Current Clamp		Order number: 000265
• 2,5 Gigabit Ethernet Interface	10/100/1000/2.5 GigE via RJ45 and SFP	Order number: 020035
• GPON Option	incl. ARGUS® GPON ONT SFP, incl. SC/LC-APC patch cable	Order number: 026076
• GPON Option, calibrated	incl. Art.No.: 026076 + initial calibration of the level measurement	Order number: 026077
• PON Installation Test	w/o stick	Order number: 026097
• Optical Light Source (1310, 1490, 1550, 1625 nm)	external	Order number: 000280
• Optical Light Source (1310, 1550 nm)	external	Order number: 000297
• Optical Loss Test incl. 2λOLS	SW option Optical Loss Test & 2λOLS: 1310 & 1550 nm	Order number: 020061
• Optical Loss Test incl. 4λOLS	SW option Optical Loss Test & 4λOLS: 1310, 1490, 1550, 1625 nm	Order number: 020062
• Optical Loss Test incl. 2λOLS & OPM-Stick	incl. Optical Light Source 1310, 1550 nm	Order number: 020063
• Optical Loss Test incl. 4λOLS & OPM-Stick	incl. Optical Light Source 1310, 1490, 1550, 1625 nm	Order number: 020064
• Optical Power Meter option (OPM)	incl. ARGUS® Optical Power Meter (SFP), type 6006	Order number: 026080
• xPON OPM + PON ID for GPON/XGS-PON		Order number: 026200
• xPON installation for GPON/XGS-PON		Order number: 026201
• GPON-ONT for xPON-OPM	incl. GPON Transceiver SFP; requires Art. No. 026200	Order number: 026202
• XGS-PON-ONT for xPON-OPM	incl. XGS-PON Transceiver SFP; requires Art. No. 026200	Order number: 026203
• xPON-4xOPM	incl. Through Mode + Up-/Downstream level measurement	Order number: 026208

data sheet: technical data subject to change.

• xPON-5xOPM	incl. Through Mode + Up-/Downstream level measurement	Order number: 026204
• Fiber Inspection option	w/o Fiber Inspection Tool	Order number: 026094
• XGS-PON option	incl. ARGUS® XGS-PON ONT SFP + SC/LC-APC patch cable	Order number: 026115
• Visual Fault Locator (VFL)	external	Order number: 000281
• XGS-PON option, calibrated	incl. Art.No. 026115 + initial calibration of level measurement	Order number: 026116
• Wi-Fi Test Interface	w/o Wi-Fi USB stick, see accessories price list*	Order number: 026059
• Wi-Fi7 module	requires Art.No.: 026059, 026054 and 026206 or 026207	Order number: 026202
• ARGUS® WLAN Analyzer	requires Art.No.: 026059	Order number: 026054
• ARGUS® 2G4 Scope (2.4 GHz Spectrum Analysis)	incl. USB 2G4 Scope stick	Order number: 000240
• VoIP Option	incl. MOS value, Call generator, NT Sim., SIP trunk	Order number: 026060
• IPTV Option	incl. IPTV STB mode, IPTV passive, channel scan	Order number: 026065
• Triple Play package	incl. VoIP and IPTV Option	Order number: 026067
• Speedtests up to 10 Gbit/s	via Ethernet (LAN4, SFP3), Wi-Fi + fiber via transceiver SFP; incl. ARGUS RealSpeed Direct (iperf); incl. Ethernet Cat6 Patch Cable 1:1 (red)	Order number: 026206
• Speedtest up to 10 Gbit/s plus xPON-5xOPM	incl. ARGUS Real Speed Direct (iperf), Ethernet Cat6 Patch Cable 1:1 (red), SC/APC (8°) to LC/APC (8°) measurement cable & dust cap	Order number: 026207
• ARGUS® Real Speed Formal (RFC6349)	incl. ARGUS® Real Speed Direct (iperf)	Order number: 026056
• ARGUS® Real Speed Direct (iperf)	Client/ Server	Order number: 026068
• ISDN BRI S/T TE Interface	requires Art.No.: 026045	Order number: 026016
• POTS Option	POTS	Order number: 026070
• SFP Support	supports various SFP types	Order number: 026042

* We would be glad to provide further details and information about additional accessories on request.

data sheet: technical data subject to change.

intec

GESELLSCHAFT FÜR
INFORMATIONSTECHNIK mbH

Rahmedestraße 90
D-58507 Lüdenscheid

Tel: +49 2351 9070-0
Fax: +49 2351 9070-70

E-Mail: sales@argus.info
Internet: www.argus.info

 www.instagram.com/intec_argus
 www.facebook.com/intec.argus
 ARGUS testing the telecom network
 <https://www.linkedin.com/company/441568>

